



DECLARATION OF PERFORMANCE

No. 003CPR2013-07-14

1. Unique identity code of the product type:

Self-locking mortise lock

2. Type, batch or serial number or another identification symbol for identification of the building product in accordance with Article 11(4) Construction Products Directive:

5495FS

3. Use intended by the manufacturer or intended uses of the building product in accordance with the harmonized technical specifications:

For doors with requirements for fire protection and smoke control

4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with Article 11(5) Construction Products Directive:

**WILKA Schliesstechnik GmbH
PO Box 100570
D-42505 Velbert**

5. If necessary, name and contact address of the authorized representative charged with the tasks in accordance with Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product in accordance with Annex V Construction Products Directive:

System 1

7. In the case of the declaration of performance relating to a construction product which is covered by a harmonized standard:

EN12209:2004

The notified test laboratory no. 1309 (PIV Velbert) carried out the type testing and issued the test report.

8. European Technical Assessment

N./N.



9. Declaration:

Important features	Declaration	Harmonized technical specification
4.2.1 Usage category	Class 3: for use by the public	DIN EN 12209: 2004
4.2.2 Long-term operational reliability	Class S: 200,000 cycles, loading of the latch bolt of 50 N	
4.2.3 Door mass and closing force	Class 3: Door mass over 200 kg (400 kg), maximum 50 N closing force	
4.2.4 Suitability for use on fire protection doors	Class 1: Suitable for use on fire protection and smoke protection doors.	
4.2.5 Security	Class 0: no security requirements	
4.2.6 Corrosion resistance and temperature	Class C: High corrosion resistance, no temperature resistance requirement	
4.2.7 Protective effect and resistance to drilling	Class 3: Average protective effect and no resistance to drilling	
4.2.8 Door-related area of use	Class B: mortice lock, swing door	
4.2.9 Type of key operation and interlock	Class A: Cylinder lock, automatic interlock	
4.2.10 Type of spindle actuation	Class 2: Lock for operating a door handle without holding spring	
4.2.11 Requirement for key identification	Class 0: no requirements	
5.1.1 (EN 12209) Control of hazardous substances	The raw materials and components used do not contain any hazardous substances nor release such substances which exceed the maximum limits specified in the existing European material standards or any statutory national regulations.	



10. The performance of the product in accordance with Numbers 1 and 2 corresponds to the declared performance in accordance with Number 9.

The manufacturer alone is responsible for issuing this declaration of performance in accordance with Number 4.

Signed for or on behalf of the manufacturer by:

Volker Mann, Product manager metalframe program / escape door systems

.....

(Name and function)

Velbert, 26.02.2014

.....

(Place and date of issue)

A handwritten signature in black ink, appearing to read "Mann", is written over a dotted line.

.....

(Signature)